



1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
工作台尺寸 Pallet dimension	500x500 mm	平臺總高度 Overall height in horizontal	280 mm												
中心孔尺寸 Center hole diameter	∅50H7	T型槽寬 Width of T-slot	18H7												
何樂馬達型號 (選配/optional)	FANUC A12i/B22is MITSUBISHI HF204S	盤面偏擺 Run out of table surface	0.02 mm												
伺服馬達 Servo motor	SIEMENS 1FK7083	上下平行度 Parallelism between table surface and table base	0.02 mm												
減速比 Transmission ratio	1:144	確認用圖													
最高迴轉速 Max. table speed	11.1 rpm	客戶確認用章													
最小設定單位 Resolution	0.001°	核准	審核												
夾緊扭力 Clamping torque	250 Kg-m														
容許切削扭矩 Cutting torque	170 Kg-m														
油壓液壓力 Hyd. pressure	50 Kg/cm ²														
分度精度 Indexing accuracy	15°														
重複精度 Repeatability	6°														
容許負載容量(平均負載) Max. table load(Average)	600 Kg														

00'00'00		XXXXXX	detron		比例 SCALE	1=5	機型 MODEL	GH500HT	材質 MATERIAL	GH500HT	名稱 TITLE	GH500外型圖	料號 PART NO.	GH500HT-A01
▲	00'00'00	XXXXXX	SKIAGRAPHY	SKIAGRAPHY	用圖 UNIT	備註 REMARKS	校準	審核	繪圖	繪圖	繪圖	繪圖	SHEET OF	A2